

LESNA Cine Matt projection surfaces are produced from specially formulated PVC to create bright images with high contrast and accurate colour rendition. Cine Matt is found in cinemas and special venues around the world. Made from welded panels, seams are not visible under normal viewing conditions. (Seams commonly run vertically)

## General

Weight: 0.095lbs/ft<sup>2</sup> (0.463kg/m<sup>2</sup>)

Max Size: 45' x 110' (13.5m x 33.5m)

Flame Retardant to:

-North America: ASTM E84, NFPA 701, CAN/ULC-S102.2

-Europe: M1, B1, BS-5867 Part 2, PN-EN ISO 6940-41

Perforation: 1mm holes; 5% open area

Edging: Grommets (eyelets) on 9" (230mm) centres with 2" (45mm) webbing

## Ordering

-LESNA calculates the surface size for Cine Frames using proprietary PVC stretch factors.

-When ordering surfaces only LESNA determines the surface size per either frame dimensions or customer specification.

## Shipping and Handling

-Crated according to size. Folded and packed in a cardboard box. Typical shipping weight is approximately 0.095lbs/ft<sup>2</sup> (0.463kg/m<sup>2</sup>).

-Transport and store surfaces between 40°F and 85°F (5°C and 30°C) with relative humidity less than 80%.

-Cold screens must be warmed to at least 68°F (20°C) to prevent cold cracking and minimize creases.

-Cine Matt surfaces should not be stored folded for longer than 45 days.

## Warranty

LESNA Cine Matt surfaces are produced under stringent quality control. We warranty Cine Matt surfaces (value of replacement materials and shipping via standard freight) against manufacturing defects for 90 days following installation.

